

T2150 Serial Matrix

Fast, reliable class leading printers



The T2150 and T2250 are highly featured, reliable and stylish machines. Performance and workload, ergonomics, maintainability, excellent price - everything has been incorporated to ensure they are the only acceptable choice for the customer.

Continuous and cut forms are fed at the front for quick and easy loading. This ensures a straight path for the forms resulting in reliable paper transportation, even on 6-part stock. Loading paper is easier. The operator does not have to fumble over or around the printer to gain access to rear located tractors. If 'tear at top of form' is inadequate for your application, the 2150S features a cutting device which separates forms automatically

User intervention is kept to a minimum with a suite of features designed to ensure the products run at optimum reliability and performance.

The product is at home in the computer room, data processing room, or in the office. An unobtrusive 52dBA acoustic rating results in a printer, which is half as quiet, compared with many competitive models.

Product Highlights

- Print speeds up to 750 cps
- 26,000 pages per month workload
- 80 columns
- 24 pin print head produces excellent print quality
- Automatic gap adjustment and quick tear
- Straight through paper path for easy forms loading
- Parallel and Serial interfaces standard
- LAN, IBM AS400/iSeries, Mainframe optional

Available Configuration:

- T2150** Standard Product
- T2150S** with Automatic cutter
- LA550N** DEC compatible version

Print Speed	Draft: 500cps; NLQ: 180cps; LQ: 90cps
Resolution	Up to 360 x 360dpi
Printhead Life	400 million characters
Standard Connectivity	Parallel (bi-directional) and serial RS232. 64Kb selectable
Optional Connectivity	Serial RS422, serial current loop (20mA), Ethernet 10/100 Base T, USB Parallel Adapter, HostCom pocket coax matrix for IBM mainframe HostCom pocket twinax for AS400, iSeries, System 3X
Standard Emulation	IBM proprinter XL24, Epson LA2550, Tally MTPL + barcode + LCP
Optional Emulation	DEC LA75; MT50 (Diskette and manual program packs)
Fonts	HS draft (sans serif), draft (sans serif), Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B*, 19 barcodes and large character printing. Range of Arabic fonts (Arabic model)
Consumables	Ribbon: 3.6 million characters
STD Paper Handling	Push tractors with paper parking and automatic gap adjustment (AGA). Cut sheet front insertion with AGA
Opt'l Paper Handling	Additional push tractor, front. Additional push tractor, rear. Front single bin automatic sheet feeder. Paper cutting device (T2150S only)
Paper Type	Continuous forms, Cut sheet
Paper Weight	Continuous forms 60-120gsm; Cut sheet 80-120gsm
Paper Size	
Physical Weight	9Kg
PhysicalSize	(HxWxD): 300x460x295mm
Power Voltage	230V
Power Consumption	40W printing
Workload	26,000 pages per month
Drivers	
Temperature	+10° to +35°C
Humidity	20% to 80%
Acoustic	53dB(A)
Warranty	1 year return to base

